

TECHNICAL FACT SHEET

		WHITE		COLOUR
STANDARD COLOURS ACCORDING TO RAL CODE		9016		RED: 3001 BLUE: 5015 GREY: 7035 BLACK: 9004
FINISH		MATT / GLOSSY		
DIMENSIONS FOIL ROLL (TOLERANCE)		WIDTH 1,22 m – LENGTH 28,68 m (+- 0,5mm)		
THICKNESS (TOLERANCE)		0,51 mm (0,03 mm)		
REACTION TO FIRE*	EN13501-1	B _L - s2, d0		B _L – s2, d0
SPECIFIC GRAVITY	ASTMD792	1460 kg/m³ - 745 g/m²		
TEMPERATURE RANGE		-25°C – 65°C		
FLEXURAL STRENGTH	ASTMD790		2009	6
TENSILE STRENGTH	ASTM D638-14		TD > 47 Mpa – MD > 48	
RUPTURE	ASTM D638-14		TD > 47 Mpa – MD > 48	
DEGRADATION	ASTM D4329		0,03	
UV-RESISTANT		YES		NO



All data and technical information are based on results obtained under typical application conditions. Recipients of the information should, in their own interest and responsibility, check with us whether the data and information apply to the intended area of application. Installation instructions can be found on our website. Isoskin accepts no responsibility for applications in which Isoskin products are used without prior permission from Isoskin. Isoskin accepts no responsibility if the products are placed incorrectly. Product changes are reserved without prior notice. Isoskin accepts no liability for any (configuration) errors or incompleteness.

*reaction to fire of the product only if fitted in combination with Isoskin tape.